

### **RGH2 DELUXE**

#### FRONT & REAR D SAFETY HARNESS

This two point safety harness offers improved comfort with the additions of a shoulder pad and leg pads.

The chest and leg straps comprise of fast fit buckles for quick donning. The two attachment points extend this harness's working capability. Meaning it can be used for fall protection and restraint situations in either vertical or horizontal planes. The ring connection between the chest and shoulder straps ensures no stress loading when force is applied to the front D ring. High contrast stitching makes inspection easier. The addition of a flexible rear D pad provides additional comfort. The inclusion of easy slide shoulder buckles increases the range of adjustment. The way the harness has been designed minimises the amount of rigid webbing edges. A variety of devices can be used with the harness, but check for suitability.

/ Front & rear attachment point

/ Fast fit buckles on chest and legs

/ Shoulder comfort pad

/ Leg comfort pads

Accredited to: EN 361:2002

Web material: 45mm RIDGE Protect anti-bacterial polyester\*

Fittings: High tensile steel alloy

Weight: 1.45kg

 $^*$  14 times reduction in bacterial growth, according to ISO 20743:2013 contact with K.pneumoniae, commonly associated with healthcare infections such as E.coli







## **RIDGEGEAR PRODUCT DATA SHEET**

# **RGH2 DELUXE**

### **FEATURES**



Fully adjustable



Rip stitch indicators



Front attachment point



Rear attachment point & shoulder pad



Fast fit buckles



Leg pads

### SIZE GUIDE

Correct sizing is essential to the safety and comfort of a safety harness. Use this table to help select the appropriate size and feel free to give us a call if you need any assistance.

Size	SMALL	STANDARD	LARGE	X-LARGE
A	36 - 42"	42 - 50"	50 - 54"	54 - 58"
Chest	91 - 107cm	107 - 127cm	127 - 137cm	137 - 147cm
B	30 - 36"	36 - 44"	44 - 48"	48 - 52"
Waist	76 - 91cm	91 - 112cm	112 - 122cm	122 - 132cm
C	38 - 44"	44 - 52"	52 - 56"	56 - 60"
Hips	97 - 112cm	112 - 132cm	132 - 142cm	142 - 152cm



