



RGHL1

TEMPORARY LIFELINE

The RGHL1 is a simple to install horizontal webbing safety line, incorporating a ratchet tensioner.

The RGHL1 safety line can be used in conjunction with fixed length or adjustable restraint and fall arrest lanyards. The assembly is supplied in its own bag complete with shoulder strap, enabling the user to carry it to site with little effort. Once fitted, the bag can be used for storing surplus webbing.

Accredited to: (EU)2016/425, EN 795:2012 Type B, EN 362: 2004, ANSI Z359.12

Kit contains: Horizontal safety line with ratchet tensioner
Anchorage sling x 2 (RGK26)
24mm twistlock steel karabiner x 2 (RGK3)
Carry bag

See overleaf for specific item specifications



RGHL1

ITEM SPECIFICATIONS

Horizontal safety line with ratchet tensioner

Accredited to: (EU)2016/425

Web material: Polyester

Webbing width: 35mm (line)

Size/weight: 10m line 3kg
20m line 4kg

Max. Users: 2 (Fall Arrest)

Product: Anchorage sling x 2 (RGK26)

Accredited to: EN 795:2012 Type B

Web material: Polyester cover and core

Breaking load: 70kN

Product: 24mm twistlock steel karabiner x 2 (RGK3)

Accredited to: EN 362:2004
ANSI Z359.12

Material: Steel

Plating: Zinc

Gate opening: 24mm

External length: 119mm

Closure type: Twistlock

MBS: 50kN

Weight: 300g

