

## ELITE twin l'yrd - oval, 1.25m, s.hooks

High load rated energy absorbing lanyards with connector & length options for a range of fall protection applications

### Features:

- High load rating, approved for users up to 140kg.
- Large central ring on twin leg versions
- Suspension intolerance relief loops
- Single and twin leg options
- High twist patented ropes
- Range of connectors and lengths
- Durable protective cover
- Unique serial ID number

Large central ring provides parking point for unused leg and prevents issues caused by 3 way loading.

Absorber will not deploy at force less than 200kg. Min. strength 1500kg after deployment.

Absorber with replaceable cover, tamper evident but with increased durability.

Suspension intolerance relief loop deploys automatically providing support for both feet.

Patented ropes allow high degree of twist in lanyard legs, minimising kinking.

Unique serial ID number allows easy management of equipment.

Code	Legs	Harness Connector	Length ***cm	Anchorage Connector
L2M***S	2	Oval	125/150/175	Scaff hook
L2T***S	2	TriAct	125/150/160/175	Scaff hook
L2T160A	2	TriAct	160	CE/ANSI hook
L2T150B	2	TriAct	150	Steplock hook
L2T170BC	2	TriAct	170	Steplock pear hook, clipback & sleeve
L2T185KC	2	TriAct	185	Twistlock, clipback & sleeve
L1T195K	1	TriAct	195	Twistlock, ring & sleeve



### Specifications:

*NB: specifications and colour may change without notice.*

Size:	1.25m
EN Test Mass:	100kg
Loading:	Additionally tested 140kg Fall factor 2
Conformity:	EN354:2010, EN355:2002, EN362:2004
Materials:	Polyester / polyamide webbing, alloy.
Weight (kg):	1.60
Industries:	Telecoms, utilities, fire and rescue service, renewables industry.

All our PPE, rescue and lifting equipment have both UKCA and CE conformity where applicable